

Extreme performance heavy duty sack (HDS) films for improved load stability

Energy lives here™




5-layer POD heavy duty sacks film

5-layer film structure

Thickness: 100 µm

- Exceed XP 8318ML
- Exceed XP 8784ML
- Enable 2005MC
- ExxonMobil HDPE



New film structure with Exceed™ XP performance PE polymers delivers:

- ⇄ Step-change downgauging
- 📦 Packaging integrity, bag drop performance for load stability
- ⚙️ Outstanding processing and output

Polymer properties	Exceed XP 8318ML	Exceed XP 8784ML	Enable 2005MC	ExxonMobil HD 7845.30	Test method* (based on)	Unit
Melt index (190°C/2.16 kg)	1.0	0.80	0.50	0.45	ASTM D1238	g/10 min
Density	0.918	0.914	0.920	0.958	ASTM D1505	g/cm ³

*For detailed product information, please consult the individual grade data sheet, available on our website: www.exxonmobilchemical.com
 Values given are typical and should not be interpreted as specifications. Data generated by or on behalf of ExxonMobil Chemical.

Discover the full story:



Portfolio of performance PE polymers:

- Exceed™ XP – when eXtreme Performance matters, for step-out mechanical performance and excellent processability
- Exceed™ – for superior performance with outstanding mechanical and sealing properties combined with best-in-class optics
- Enable™ – for optimum solutions, providing excellent bubble stability with HAO properties

Tomorrow's performance today.

For more information: exxonmobilchemical.com/HDS

©2021 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

