



## Introducing SpectraSyn Plus™ 5, ExxonMobil Product Solutions' latest polyalphaolefin (PAO) base stock

SpectraSyn Plus 5 is just the latest offering in ExxonMobil Product Solutions' portfolio. If your challenge is to formulate top-tier automotive lubricants that meet the current trends for lower viscosity and lower volatility, then we have the solution.

Grade	SG at 15.6/15.6°C	KV at 100°C cSt	KV at 40°C cSt	VI	Pour point °C	CCS at -35°C	NOACK volatility, wt%	Flash point (COC) °C
	ASTM D4052	ASTM D445	ASTM D445	ASTM D2270	ASTM D97 / D5950	ASTM 5293	ASTM D5800 / DIN51581	ASTM D92
<b>SpectraSyn Plus 5</b>	<b>0.825</b>	<b>5.2</b>	<b>25.4</b>	<b>144</b>	<b>&lt;-57</b>	<b>2400</b>	<b>&lt;8</b>	<b>239</b>
SpectraSyn Plus 3.6	0.816	3.6	15.4	120	<-65	1,050	<17	224
SpectraSyn Plus 4	0.820	3.9	17.2	126	<-60	1,290	<12	228
SpectraSyn Plus 6	0.827	5.9	30.3	143	<-54	3,600	<6	246

### Performance benefits



Low volatility for extended drain intervals



Low CCS viscosity for better engine starting and low temperature oil flow



Improved energy efficiency

### Your source for advanced synthetics

For an extensive range of advanced synthetic lubricant base stocks, you need an innovative supplier – ExxonMobil Product Solutions. With our broad range of SpectraSyn™ polyalphaolefin (PAO), Synesstic™ alkylated naphthalene (AN) and Esterex™ ester base stocks, we provide reliable, global base stock solutions that can help you achieve your business goals.

### Let us work together to energize your innovation.

Please contact your local sales representative for sourcing information.

©2022 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.