

Achieving formulations meeting CLP¹ classification thresholds for cumene and naphthalene

Did you know?

The European Union has defined the most stringent carcinogen classifications through the implementation of the CLP regulation.

At ExxonMobil, we fine-tune our manufacturing process to reduce cumene content to <0.1wt% and naphthalene content <1wt% to offer:

- **Ultra-low cumene (ULC): Solvesso™ 100 ULC**
- **Naphthalene-depleted (ND): Solvesso™ 150 ND**

EU CLP Classification Rule

Cumene

Carcinogen
Category 1B

0.1%
threshold

Naphthalene

Carcinogen
Category 2

1%
threshold

Source: EU ECHA Chemicals Database – <https://chem.echa.europa.eu/>

Why choose Solvesso™ ULC and ND fluids?



Not labelled as carcinogenic according to current CLP provisions:

- Cumene content < 0.1wt%
- Naphthalene content < 1 wt%

Why choose ExxonMobil?



Worldwide supply excellence

- Available globally
- World-scale integrated petrochemical facilities



Enable product development

- Experts ready to assist you through your formulation needs

Solvesso™ fluids: Specially formulated portfolio

Carbon range	Grade	Boiling Range (°C)	Flash Point (°C)	Cumene (wt%)
C9	Solvesso 100	161-174	49	<1
	Solvesso 100 ULC	167-179	52	<0.1

Carbon range	Grade	Boiling Range (°C)	Flash Point (°C)	Naphthalene (wt%)
C10	Solvesso 150	182-204	49	<5
	Solvesso 150 ND	180-192	64	0.6
C11	Solvesso 200	227-285	103	6
	Solvesso 200 ND	244-293	114	0.7
	Solvesso 200 ULN	240-283	110	<0.1

*Typical qualities of Solvesso™ fluids sold in Asia Pacific

The right grade for each application



Agricultural chemicals



Paints & coatings



Oilfield chemicals



Chemical processes & more

Solvesso™ aromatic fluids deliver high-performance solutions tailored for a wide range of industrial applications. Each product is engineered to offer high solvency and remarkable versatility.



Have a technical question?

Connect directly with our technical experts at exxonmobilchemical.com/AnswerPerson

©2025 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.



ExxonMobil