

Product Safety Summary



EXX-PRINT™ 74 A-S

This Product Safety Summary document is a high-level summary intended to provide the general public with an overview of product safety information on this chemical substance. It is not intended to provide emergency response, medical or treatment information, or to provide a discussion of all safety and health information. This document is not intended to replace the (Material) Safety Data Sheet. Warnings and handling precautions provided below are not intended to replace or supersede manufacturers' instructions and warning for their consumer products which may contain this chemical substance.

1. Chemical Identity (Mixture)

<u>CAS No.</u>	<u>Chemical Name:</u>
64742-81-0	Kerosine (Petroleum), Hydrodesulfurized
64742-47-8	Distillates (petroleum), hydrotreated light
<u>EC NO.:</u>	
920-360-0	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)
927-632-8	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

The EC # applies in REACH countries while the CAS number is the identifier in the rest of the world.

2. Product Uses

Exx-Print hydrocarbon fluids in printing ink formulations help printers achieve fast cycle times and quality reproduction. Used to formulate inks for offset printing processes including heat set (web feed) and quick set (sheet feed).

3. Physical / Chemical Properties

Exx-Print 74 A-S is a non-hazardous material. The material is classified as a static accumulator. Although the material has a relatively low vapor pressure, it should be handled only with adequate ventilation.

The flash point for this product is approximately 120°C/ 248°F.

4. Health Information

Exx-Print M 74 A-S is generally recognized to have low acute toxicity if ingested, inhaled or after skin contact. This material is expected to present a low risk for chronic toxicity. Concentrations above the occupation exposure limit of 55 ppm in the air can cause eye, nose, throat, and lung irritation in humans. Symptoms of Exx-Print 74 A-S over exposure may include flushing, headache, dizziness, central nervous system (CNS) depression, nausea, vomiting, anesthesia, and coma. If this occurs, seek immediate medical attention. Repeated dermal exposure may cause skin dryness and cracking. This product is not regarded as a mutagen, a carcinogen, or a concern for chronic reproductive or developmental effects. High vapor concentrations may cause drowsiness and dizziness and may cause CNS depression, but Exx-Print M 74 A-S is not expected to have any neurotoxic effects beyond acute CNS depression.

Product Safety Summary



EXX-PRINT™ 74 A-S

5. Additional Hazard Information

If accidentally swallowed, small amounts of liquid may be aspirated into the lungs during ingestion or from vomiting which may cause severe lung inflammation and lung edema (an accumulation of fluid in the lungs). This is a medical emergency which must be immediately and properly treated. Do not induce vomiting.

6. Food Contact Regulated Uses

This product is not claimed as compliant for food contact uses.

7. Environmental Information

Exx-Print 74 A-S biodegrades at a moderate rate and will not persist in the environment. It is not expected to cause short-term toxicity to fish or other aquatic organisms. Because of its low solubility in water and volatility (tendency to move from water to air) chronic aquatic toxicity is not expected; however a significant spill may cause long-term adverse effects in the aquatic environment. It is rapidly degraded in air. Considerable measures are taken to prevent its release to the atmosphere and minimize any exposure to the environment from manufacturing and use activities.

8. Exposure Potential

- **Workplace exposure** – This refers to potential exposure in a manufacturing facility or through evaporation in various industrial applications. Generally, exposure of personnel in manufacturing facilities is relatively low because the process, storage and handling operations are enclosed. The ExxonMobil recommended occupational exposure limit (OEL) is 55 ppm per 8-hour work day.
- **Consumer use of products containing Exx-Print 74 A-S** – If exposure should occur, it is likely to be infrequent and of short duration depending on the products used and the conditions under which they are used. The best way to prevent exposure to vapors is to work in well-ventilated areas, wear chemical resistant gloves, and follow good personal hygiene practices.
- **Environmental releases** – As a chemical manufacturer, we are committed to operating in an environmentally responsible manner everywhere we do business. Our efforts are guided by in-depth scientific understanding of the environmental impact of our operations, as well as by the social and economic needs of the communities in which we operate. Industrial spills or releases are rare; however a spill may pose a significant flammability issue. Our operational improvement targets and plans are based on driving incidents with real environmental impact to zero and delivering superior environmental performance.

9. Manufacture of Product

- **Process** – Mixture

10. Risk Management

- **Workplace Risk Management** – When using this product, make sure that there is adequate ventilation. Always use chemical resistant gloves to protect your hands and skin and always wear eye protection such as chemical goggles. Do not eat, drink, or smoke where chemicals are handled, processed, or stored. Wash hands and skin following contact. If this product gets into your eyes, rinse eyes thoroughly for at least 15 minutes with tap water and seek medical attention. Please refer to the (Material) Safety Data Sheet.

Product Safety Summary



EXX-PRINT™ 74 A-S

- **Consumer Risk Management** - This chemical is not sold directly to the public for general consumer uses. If exposure should occur, it is expected to be infrequent and of short duration. Always follow manufacturers' instructions, warnings and handling precautions when using their products. The best way to minimize exposure to vapors is to work in well-ventilated areas.

11. Regulatory Information

Regulations may exist that govern the manufacture, sale, transportation, use and/or disposal of this chemical and may vary by city, state, country or geographic region. Additional helpful information may be found by consulting the relevant ExxonMobil (Material) Safety Data Sheet at:

- <http://www.msds.exxonmobil.com>

12. Conclusion Statements

Exx-Print 74 A-S

- is low in toxicity; however it may cause lung damage if swallowed.
- does not cause adverse health or environmental effects at levels typically found in the workplace or environment.
- should be used only with good ventilation; avoid all ignition sources.

©2018 ExxonMobil. The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. Users of chemical products should refer to the product labels and applicable Material Safety Data Sheets for information and recommendations as to the safe handling and use of this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest. ExxonMobil, the ExxonMobil Logo and the "Interlocking X" Device, and product names used herein are trademarks or registered trademarks of Exxon Mobil Corporation and/or its affiliates, unless otherwise noted.