

This Product Safety Summary document is a high-level summary intended to provide the general public with an overview of product safety information on this chemical substance. It is not intended to provide emergency response, medical or treatment information, or to provide a discussion of all safety and health information. This document is not intended to replace the (Material) Safety Data Sheet. Warnings and handling precautions provided below are not intended to replace or supersede manufacturers' instructions and warning for their consumer products which may contain this chemical substance.

1. Chemical Identity

CAS No.

72480-45-6

Chemical Name:

Fatty acids, C9-28-neo-

2. Product Uses

Neo Acid 919 is used primarily as an intermediate to make other chemical products such as paint dryers and stabilizers.

3. Physical / Chemical Properties

Neo Acid 910 is a pale yellow liquid. The flash point is approximately 216°F /102°C.

4. Health Information

Exposure to Neo Acid 919 may result in eye, skin, or respiratory irritation. Elevated temperatures or mechanical action has the potential to form vapors, which are irritating. Neo Acid 919 is considered minimally toxic when inhaled or contacted via the skin (may cause drying leading to discomfort and dermatitis). Slight toxicity related to the irritating nature of the chemicals can occur when ingested. Contact with the eyes may cause mild, short lasting discomfort.

5. Additional Hazard Information

Material can accumulate static charges which may cause an ignition.

6. Food Contact Regulated Uses

This product is not claimed as compliant for food contact uses.

7. Environmental Information

Neo Acid 919 released to the environment is expected to partition largely to water. Neo Acid 919 biodegrades slowly and therefore may pose long-term adverse effects in the aquatic environment. Therefore, care should be taken to minimize any exposure to the environment from manufacturing or use activities. Neo Acid 919 is not expected to bioaccumulate.

8. Exposure Potential

- **Workplace exposure** – This refers to potential exposure in a manufacturing facility or through evaporation in various industrial applications. Generally, exposure of personnel in manufacturing facilities is relatively low because the process, storage and handling operations are enclosed. The ExxonMobil occupational exposure limit (OEL) value is 25 mg/m³ per an 8-hour work day.
- **Consumer use of products containing Neo Acid 919** – This category of exposure is highly variable depending on the products used and the conditions under which they are used. Because Neo Acid 919 is primarily converted into other chemicals exposure of the majority of consumers to commercial sources is likely to be infrequent and of short duration. The best way to prevent exposure to vapors is to work in well-ventilated areas, wear chemical resistant gloves, and follow good personal hygiene practices.
- **Environmental releases** – As a chemical manufacturer, we are committed to operating in an environmentally responsible manner everywhere we do business. Our efforts are guided by in-depth scientific understanding of the environmental impact of our operations, as well as by the social and economic needs of the communities in which we operate. Industrial spills or releases are rare; however a spill may pose a flammability issue. Our operational improvement targets and plans are based on driving incidents with real environmental impact to zero and delivering superior environmental performance.

9. Manufacture of Product

- **Process** – produced by reacting a branched olefin with carbon monoxide and water at elevated temperatures and pressures in the presence of an acid catalyst.

10. Risk Management

- **Workplace Risk Management** – When using this product, make sure that there is adequate ventilation. Always use chemical resistant gloves to protect your hands and skin and always wear eye protection such as chemical goggles. Do not eat, drink, or smoke where chemicals are handled, processed, or stored. Wash hands and skin following contact. If this product gets into your eyes, flush eyes thoroughly with tap water. If irritation occurs, get medical assistance. Please refer to the (Material) Safety Data Sheet.
- **Consumer Risk Management** - This chemical is not sold directly to the public for general consumer uses. If exposure should occur, it is expected to be infrequent and of short duration. Always follow manufacturers' instructions, warnings and handling precautions when using their products. The best way to minimize exposure to vapors is to work in well-ventilated areas.

11. Regulatory Information

Regulations may exist that govern the manufacture, sale, transportation, use and/or disposal of this product and may vary by city, state, country or geographic region. Additional helpful information may be found by consulting the relevant ExxonMobil (Material) Safety Data Sheet at:

- <http://www.msds.exxonmobil.com>

12. Conclusion Statement

Neo Acid 919 ...

- is low in acute toxicity; however, repeated dermal exposure may cause skin dryness and cracking.
- does not cause adverse health or environmental effects at levels typically found in the workplace or environment.

Product Safety Summary



ExxonMobil™ Neo Acid 919

- is not combustible and has a low vapor pressure.

©2018 ExxonMobil. The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. Users of chemical products should refer to the product labels and applicable Material Safety Data Sheets for information and recommendations as to the safe handling and use of this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest. ExxonMobil, the ExxonMobil Logo and the "Interlocking X" Device, and product names used herein are trademarks or registered trademarks of Exxon Mobil Corporation and/or its affiliates, unless otherwise noted.