

# Product Safety Summary

Solvesso™ 200 (Fluid)



This Product Safety Summary document is a high-level summary intended to provide the general public with an overview of product safety information on this chemical substance. It is not intended to provide emergency response, medical or treatment information, or to provide a discussion of all safety and health information. This document is not intended to replace the (Material) Safety Data Sheet. Warnings and handling precautions provided below are not intended to replace or supersede manufacturers' instructions and warning for their consumer products which may contain this chemical substance.

## 1. Chemical Identity

**CAS No:** 64742-94-5      **Chemical Name:** Solvent Naphtha (Petroleum), Heavy Aromatic

**EC No :** 926-273-4      **Chemical Name:** Hydrocarbons, C10-13, aromatics, >1% naphthalene

The EC # applies in REACH countries while the CAS number is the identifier in the rest of the world.

## 2. Product Uses

Solvesso 200 is a liquid solvent used in industrial applications such as fuel additives, paints and coatings, agricultural pesticides, foundry resins, industrial cleaning, process fluids and solvent applications. It is not sold directly to the public for general consumer uses; however, this product may be an ingredient in consumer and commercial product applications such as paints and coatings.

## 3. Physical / Chemical Properties

Solvesso 200 has a relatively low vapor pressure and should be handled only with adequate ventilation. The flash point for Solvesso 200 is greater than 214°F /101°C.

## 4. Health Information

Solvesso 200 is generally recognized to have low acute and chronic toxicity if ingested and/or breathed. Vapor concentrations above the exposure limit of 8 parts per million (ppm) in the air can cause eye and lung irritation and may cause headaches, dizziness, drowsiness or CNS depression. Prolonged or repeated skin contact in an occupational setting may result in skin dryness or irritation and in these situations, the use of chemical resistant gloves is recommended. This product is not regarded as a mutagen and there is low concern for reproductive or developmental effects. It is suspected of causing cancer as it contains naphthalene, which has been classified as a possible human carcinogen based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.

## 5. Additional Hazard Information

If accidentally swallowed, small amounts of liquid may be aspirated into the lungs during ingestion or from vomiting, this may cause severe lung inflammation and lung edema (an accumulation of fluid in the lungs). This is a medical emergency which must be immediately and properly treated. Do not induce vomiting.

# Product Safety Summary

Solvesso™ 200 (Fluid)



## 6. Food Contact Regulated Uses

This product is not claimed as compliant for food contact uses.

## 7. Environmental Information

Solvesso 200 is toxic to the aquatic environment. If accidentally spilled in the environment, it is potentially a threat to the environment due to its moderate toxicity to aquatic organisms (e.g. fish and invertebrates). Because of its low solubility in water and volatility (tendency to move from water to air) chronic aquatic toxicity is not expected, however a significant spill may cause long-term adverse effects in the aquatic environment. Solvesso 200 is readily biodegradable and thus not expected to persist in the environment. Solvesso 200 is a volatile organic compound (VOC) and is rapidly degraded in air, water, and soil. Considerable measures are taken to prevent its release to the atmosphere and minimize any exposure to the environment from manufacturing and use activities.

## 8. Exposure Potential

Based on the uses for Solvesso 200, the public could be exposed through:

- **Workplace exposure** – This refers to potential exposure in a manufacturing facility or through evaporation in various industrial applications. Generally, exposure of workers in manufacturing facilities is relatively low because the process, storage and handling operations are enclosed. The ExxonMobil recommended occupational exposure limit value is 15 parts per million (ppm) per 8-hour work day.
- **Consumer use of products containing Solvesso 200** – If exposure should occur, it is likely to be infrequent and of short duration depending on the products used and the conditions under which they are used. Exposure could occur through the use of cleaning agents or coatings formulations that contain this product. The best way to prevent exposure to vapors is to work in well-ventilated areas, wear chemical resistant gloves, and follow good personal hygiene practices.
- **Environmental releases** – As a chemical manufacturer, we are committed to operating in an environmentally responsible manner everywhere we do business. Our efforts are guided by in-depth scientific understanding of the environmental impact of our operations, as well as by the social and economic needs of the communities in which we operate. Industrial spills or releases are rare; however a spill may pose a significant flammability issue. Our operational improvement targets and plans are based on driving incidents with real environmental impact to zero and delivering superior environmental performance.

## 9. Manufacture of Product

**Process** – Aromatic Fluids are characterized as a complex mixture of aromatic hydrocarbons obtained from crude oil by fractionation and reforming.

They have an aromatic content of 99% or greater. Processes and equipment for manufacture, transfer and storage are continuous and enclosed

## 10. Risk Management

- **Workplace Risk Management** – When using this substance or products which contain this substance, make sure that there is adequate ventilation. Always use chemical resistant gloves to protect your hands and skin and always wear eye protection such as chemical goggles. Do not eat,

# Product Safety Summary

Solvesso™ 200 (Fluid)

**ExxonMobil**  
Chemical

drink, or smoke where chemicals are handled, processed, or stored. Wash hands and skin following contact. If this product gets into your eyes, flush eyes thoroughly for at least 15 minutes with tap water. If irritation occurs, get medical assistance. Please refer to the Safety Data Sheet.

- **Consumer Risk Management** - This chemical is not sold directly to the public for general consumer uses. If exposure should occur, it is expected to be infrequent and of short duration. Always follow manufacturers' instructions, warnings and handling precautions when using their products. The best way to minimize exposure to vapors is to work in well-ventilated areas.

## 11. Regulatory Information

Regulations may exist that govern the manufacture, sale, transportation, use and/or disposal of this product and may vary by city, state, country or geographic region. Additional helpful information may be found by consulting the relevant ExxonMobil Safety Data Sheet at:

- <http://www.msds.exxonmobil.com>

## 12. Conclusion

Solvesso200

- a. is a widely used industrial and agricultural solvent.
- b. has low acute toxicity; however, it may cause lung damage if swallowed, and is suspected of causing cancer.
- c. does not cause adverse health or environmental effects at levels typically found in the workplace or environment.
- d. has a low vapor pressure; use only with good ventilation.

*©2021 ExxonMobil. The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. Users of chemical products should refer to the product labels and applicable Material Safety Data Sheets for information and recommendations as to the safe handling and use of this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest. ExxonMobil, the ExxonMobil Logo and the "Interlocking X" Device, and product names used herein are trademarks or registered trademarks of Exxon Mobil Corporation and/or its affiliates, unless otherwise noted.*