





The material also becomes more flexible when RCP is dry blended with Vistamaxx™ 3000 or Vistamaxx 6202. Flexibility increases with the dosage of Vistamaxx performance polymers.

Figure 2: Flexural modulus



The clarity, light transmittance and haze of the original material are virtually the same when RCP is dry blended with 30 percent Vistamaxx 3000 or Vistamaxx 6202.

Figure 3: Optical properties - 30% Vistamaxx polymers blended with RCP: 1 mm thick discs



### Enhanced products

Freezing tests, undertaken by Lisi, indicate that modifying RCP with a small percentage of Vistamaxx polymers improves impact strength of the container lid, even at temperatures between 0°C (32°F) and minus 20°C (minus 4°F).

Meanwhile, Lisi's cornering fatigue tests show that Vistamaxx polymers deliver improved hinge flexibility which contributes to the durability of the lid.

Of all the additives tested by Lisi, only Vistamaxx polymers increased lid hinge impact strength during the freezing test, maintained clarity and reduced stress whitening. Easy to use, Vistamaxx polymers can be dry blended with the RCP before injection molding. This is done on existing equipment without additional investment in equipment or technology.

Vistamaxx polymers can also enhance the elasticity of RCP used in the body of the food container. This can improve the seal structure of the container. Because the body is softer, the harder lid can seal without the use of seal rings. This design simplification can result in a 10 percent manufacturing cost reduction.

Vistamaxx polymers are also compliant with many international food contact regulations, such as US FDA, EU and JOSPFA, and is on the Chinese Positive List for resins permitted in food packaging products. This saves time, as no pre-qualification of the material is required and speeds up time to market.

Item	Freezing test	Cornering fatigue test
Conditions	<ul style="list-style-type: none"> <li>Sample lid cooled to -20°C for four hours before the test</li> <li>Sample dropped to the ground from a height of 76 cm</li> </ul>	<ul style="list-style-type: none"> <li>Room temperature</li> <li>Open/close the hinge 100,000 times</li> </ul>
Results	No breakage of the lid	No hinge breakage
References	Samples using other toughening agents are likely to break in this test	Industry standard: no breakage after opening/closing 10,000 times

### Better performance, increased sales

Using Vistamaxx polymers to modify RCP has enabled Lisi to offer food container lids with improved durability while remaining transparent. This has increased the company's competitiveness in the food container industry and, as a result, Lisi's food containers have enjoyed a significant growth in sales.

"Due to the balance of physical properties delivered by Vistamaxx polymers, the quality and performance of our food container lids have improved significantly. We will use Vistamaxx polymers in other applications," said Mr. Qinghua Zeng, R&D Manager, Ningbo Lisi Houseware Co., Ltd.

©2015-2019 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

Contact us for more information:  
[exxonmobilchemical.com/vistamaxx](http://exxonmobilchemical.com/vistamaxx)

