

# Exxsol™ D40 Naphtha Anti-Static

## Dearomatized Fluid

### Product Description

Low odor dearomatized hydrocarbon fluid suitable for:

- Aerosols
- Blanket wash
- Cleaning
- Coatings
- Consumer products
- Metalworking
- Mold release agent

### General

Specification Region                      ▪ North America

Properties	Minimum	Maximum	Unit	Test Method
Aniline Point	60.0	72.0	°C	ECIM 1010 ASTM D611 (mod)
Appearance	Bright & Clear	--		ECIM 1001 ASTM D4176 (mod)
Aromatic Content	--	0.85	vol%	ASTM D6379
Color, Saybolt	30	--		ASTM D6045 ECIM 1002
Flash Point (TCC)	40	--	°C	ASTM D56 (mod) ECIM 1007
Specific Gravity (15.6/15.6°C)	0.770	0.800		ECIM 1028
Sulfur Content	--	1	wppm	ASTM D5453 ECIM 2033

Distillation	Minimum	Maximum	Unit	Test Method
Distillation Range				ECIM 1006
Initial Boiling Point (IBP)	152	--	°C	ASTM D86 (mod)
Dry Point (DP)	--	204	°C	

### Notes

Stadis Anti-Static Additive has been added at the rate of 16ml/1000 gallons

ExxonMobil's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. ExxonMobil reserves the right to use other equivalent test methods in certifying this product.

For additional technical, sales and order assistance: [Contact Us](#)

©2025 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Product Solutions" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

[exxonmobilchemical.com](http://exxonmobilchemical.com)