

Solvesso™ 200

Aromatic Fluid

Product Description		Key Features	
High solvency C11 aromatic fluid, suitable for: Agricultural chemicals Coatings Fuel Additives Foundry resin Oilfield and refinery chemicals		High solvency power and high flash point	
General			
Availability ¹	▪ Africa & Middle East	▪ Europe	
Revision Date	▪ 03/01/2020		
Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Aniline Point, Mixed	13 °C	13 °C	ASTM D611
Appearance	Bright & Clear	Bright & Clear	EC A-A01
Aromatic Content	> 99 wt%	> 99 wt%	GC1
Benzene Content	≤1 mg/kg	≤1 mg/kg	GC2
Color, ASTM	0.5	0.5	ASTM D1500 ASTM D6045
Density (15°C)	990 kg/m ³	990 kg/m ³	ISO 12185
Flash Point	103 °C	103 °C	ASTM D93
Refractive Index (20°C)	1.589	1.589	ASTM D1218
Viscosity			ASTM D7042
25°C	2.74 mm ² /s	2.74 mm ² /s	
40°C	2.00 mm ² /s	2.00 mm ² /s	
Composition	Typical Value (English)	Typical Value (SI)	Test Based On
1-Methylnaphthalene	10 wt%	10 wt%	GC3
2-Methylnaphthalene	20 wt%	20 wt%	GC3
Naphthalene	6 wt%	6 wt%	GC3
Distillation	Typical Value (English)	Typical Value (SI)	Test Based On
Distillation Range			ASTM D86
Initial Boiling Point (IBP)	230 °C	230 °C	
Final Boiling Point (FBP)	284 °C	284 °C	

Notes

Typical properties: these are not to be construed as specifications.

The values indicated in this document may deviate from the test method requirements by the number of significant figures shown.

Typical values may be calculated based upon measured values of blend components, if applicable.

Values may be determined by one or more ExxonMobil test methods equivalent to industry standard test methods.

Applicable sampling and testing methods are subject to change without notice and are available for review on request.

Product may contain approximately 25 mg/kg BHT.

¹ Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

Solvesso™ 200

Aromatic Fluid

For additional technical, sales and order assistance: www.exxonmobilchemical.com/ContactUs

©2020 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

exxonmobilchemical.com