

SAFETY DATA SHEET

ExxonMobil

EXX-PRINT™ M 71 A

Section 1. Identification

Product name : EXX-PRINT™ M 71 A
Product description : Aliphatic, Cycloparaffinic, Aromatic Hydrocarbons

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Printing ink solvent
Uses advised against : This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

Supplier : ExxonMobil Petroleum & Chemical BV
POLDERDIJKWEG
Antwerpen B-2030 Belgium

24 Hour Emergency Telephone : +44 20 3885 0382 / +1-703-527-3887 (CHEMTREC)

Supplier General Contact : + 32 2 239 3111

E-Mail : SDS-CC@exxonmobil.com

Section 2. Hazard identification

Classification of the substance or mixture : Asp. Tox. 1, H304

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H304 - May be fatal if swallowed and enters airways.

Precautionary statements

Response : P301 + P331, P310 - IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains : Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%) and distillates (petroleum), hydrotreated middle

Supplemental label elements : EUH066 - Repeated exposure may cause skin dryness or cracking.

Other hazards which do not result in classification : None known.

Nota : This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	Identifiers
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)	≥75 - ≤90	REACH #: 01-2119448343-41 EC: 920-360-0 CAS: -
distillates (petroleum), hydrotreated middle	≥25 - ≤50	REACH #: 01-2119457736-27 EC: 927-632-8 CAS: -

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Section 4. First-aid measures

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products : Incomplete combustion products, Oxides of carbon, Smoke, Fume

Special protective actions for fire-fighters : Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent re-ignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Static Accumulator** : This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

- Loading/Unloading Temperature** : Ambient

- Transport Temperature** : Ambient

- Transport Pressure** : Ambient

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

- Storage Temperature** : Ambient

- Storage Pressure** : Ambient

- Suitable Containers/Packing** : Tank Trucks, Railcars, Barges, Drums, Tank Cars, Tankers

- Suitable Materials and Coatings** : Carbon Steel, Stainless Steel, polyethylene, polypropylene, Polyester, Teflon

- Unsuitable Materials and Coatings** : Natural Rubber, butyl rubber, Ethylene-propylene-diene monomer (EPDM), Polystyrene

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
EXX-PRINT™ M 71 A kerosine (petroleum), hydrodesulphurised distillates (petroleum), hydro- treated light	ExxonMobil (COMPANY) RCP - TWA: 44 ppm (Total Hydrocarbons). Form: Vapour.. RCP - TWA: 400 mg/m ³ (Total Hydrocarbons). Form: Vapour.. ACGIH TLV (United States, 1/2024) [Kerosene] Absorbed through skin. TWA 8 hours: 200 mg/m ³ (as total hydrocarbon vapor). ExxonMobil (COMPANY) Absorbed through skin. TWA 8 hours: 5 mg/m ³ . Form: Stable Aerosol.. TWA 8 hours: 200 mg/m ³ . Form: Vapour.. ACGIH TLV (United States, 1/2024) [Kerosene] Absorbed through skin. TWA 8 hours: 200 mg/m ³ (as total hydrocarbon vapor).

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A)

Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid. [Clear]
Colour	: Colorless to Yellow
Odour	: Slight
Odour threshold	: Not available.
pH	: Not applicable.
Melting point/freezing point	: Not available.
Boiling point or initial boiling point and boiling range	: 258 to 298°C (496.4 to 568.4°F) [ASTM D86]
Flash point	: Closed cup: 120°C (248°F) [ASTM D-93]
Evaporation rate	: <0.01 (butyl acetate = 1) [Calculated]
Flammability	: Ignitable
Lower and upper explosion limit/flammability limit	: Lower: 0.4% [Extrapolated] Upper: 5%
Vapour pressure	: 0.01 mm Hg [20 °C] [Calculated]
Relative vapour density	: 7.5 [Air = 1] [Calculated]
Relative density	: 0.84 [Calculated]
Density	: 0.839 g/cm ³ [15°C (59°F)] [ISO 12185]
Solubility in water	: Negligible
Partition coefficient: n-octanol/water	: >4 [Estimated]
Auto-ignition temperature	: 221°C (429.8°F) [Extrapolated]
Decomposition temperature	: Not applicable.
Viscosity	: 3.2 cSt [40 °C] [Calculated] 5.2 cSt [20 °C]
Molecular weight	: 218
<u>Particle characteristics</u>	
Median particle size	: Not applicable.
Pour point	: <-18°C [Calculated]
Hygroscopic	: No
Coefficient of Thermal Expansion	: 0.00081 per Deg C

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Excessive heat.
Incompatible materials	: Strong oxidisers

Section 10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
EXX-PRINT™ M 71 A	Rabbit - Dermal - LD50 >5000 mg/kg Rat - Oral - LD50 >5000 mg/kg Rat - Inhalation - LC50 Vapour >5000 mg/m ³ [4 hours]

Conclusion/Summary

- Inhalation** : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403
- Dermal** : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
- Oral** : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401

Irritation/Corrosion

Conclusion/Summary

- Skin** : May dry the skin leading to discomfort and dermatitis. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404
- Eyes** : May cause mild, short-lasting discomfort to eyes. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405
- Respiratory** : Negligible hazard at ambient/normal handling temperatures. No end point data for material.

Respiratory or skin sensitization

Conclusion/Summary

- Skin** : Not expected to be a skin sensitizer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406
- Respiratory** : Not expected to be a respiratory sensitizer. No end point data for material.

Mutagenicity

Conclusion/Summary

- : Not expected to be a germ cell mutagen. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 474 475 476 478 479

Carcinogenicity

Conclusion/Summary

- : Not expected to cause cancer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 453

Reproductive toxicity

Conclusion/Summary

- : Not expected to be a reproductive toxicant. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 413 414 415 416

Specific target organ toxicity (single exposure)

Conclusion/Summary

- : Not expected to cause organ damage from a single exposure. No end point data for material.

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Product/ingredient name	Category	Target organs
EXX-PRINT™ M 71 A	Not applicable.	-

Conclusion/Summary : Not expected to cause organ damage from prolonged or repeated exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 413

Aspiration hazard

Product/ingredient name	Result
EXX-PRINT™ M 71 A	Category 1

Conclusion/Summary : May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material. Data available. Based on test data for the material.

Other information

Product : Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

Toxicity

Product/ingredient name	Result
EXX-PRINT™ M 71 A	Acute - NOEL Algae - <i>Pseudokirchneriella subcapitata</i> 0.1 mg/l - data for similar materials [72 hours]
	Acute - EL50 Algae - <i>Pseudokirchneriella subcapitata</i> 1000 mg/l - not toxic at water solubility [72 hours]
	Acute - LL0 Fish - <i>Fish</i> 1000 mg/l - not toxic at water solubility [96 hours]
	Acute - EL0 Invertebrate - <i>Invertebrate</i> 1000 mg/l - not toxic at water solubility [48 hours]
	Chronic - NOEL Fish - <i>Brachydanio rerio</i> 1000 mg/l - data for similar materials [21 days]
	Chronic - LL0 Fish - <i>Brachydanio rerio</i> 1000 mg/l - not toxic at water solubility [21 days]
	Chronic - NOEL daphnia - <i>Daphnia magna</i> 17 mg/l - data for similar materials [21 days]
	Chronic - EL50 daphnia - <i>Daphnia magna</i> 1400 mg/l - not toxic at water solubility [21 days]

Section 12. Ecological information

Conclusion/Summary

- Acute toxicity** : Not expected to be harmful to aquatic organisms.
Chronic toxicity : Not expected to demonstrate chronic toxicity to aquatic organisms

Persistence and degradability

Product/ingredient name	Result
EXX-PRINT™ M 71 A	Ready Biodegradability >60% [28 days]

- Biodegradability** : Material -- Expected to be readily biodegradable.
Hydrolysis : Material -- Transformation due to hydrolysis not expected to be significant.
Photolysis : Material -- Transformation due to photolysis not expected to be significant.
Atmospheric Oxidation : Material -- Expected to degrade rapidly in air

Bioaccumulative potential

Not determined.

Mobility in soil

- Mobility** : Material -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land.

Other ecological information

- Other adverse effects** : No known significant effects or critical hazards.

Section 13. Disposal considerations

- Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Section 14. Transport information

	ADR	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 14. Transport information

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIC)	: All components are listed or exempted.
Canada inventory (DSL-NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Japan inventory (CSCL)	: All components are listed or exempted.
Japan inventory (Industrial Safety and Health Act)	: Not determined.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
United States inventory (TSCA 8b)	: All components are active or exempted.

The national inventory listings are based on the CAS number or numbers listed below.

64742-47-8; 64742-81-0

Section 16. Other information

History

Date of issue/Date of revision : 8/4/2025

Date of previous issue : 26 August 2024

Version : 2.03

Key to abbreviations

: ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group

Section 16. Other information

UN = United Nations

Procedure used to derive the classification

Asp. Tox. 1, H304

Calculation method

References : Not available.

✔ Indicates information that has changed from previously issued version.

Product code : 1162600

Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil"" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."